



WARNING



Fire, explosion and high pressure hazards

To minimize the risk of serious injury, death or property damage, follow these instructions and safety precautions at all times while using the Oxi-King™ system:

- ⇒ Read, understand and follow all instructions and safety precautions in the manual, on this label and on any label for chemicals used with this system.
- ⇒ Do not exceed maximum operating pressure of 50 psi.
- ⇒ Do not exceed maximum operating temperature of 120° F
- ⇒ Do not open under pressure. Close isolation valves and bleed off pressure before opening.
- ⇒ Do not install automatic or fast shut off valves downstream of feeder.
- ⇒ If the unit is isolated and not vented or drained, install a relief valve to bleed off any pressure that builds up.
- ⇒ Do not leave inlet and outlet closed for extended periods unless unit is drained and cap is open.
- ⇒ USE ONLY Oxi-King™ Brom Pac. DO NOT USE any other pack or bulk chemical in the Oxi-King™ System.
- ⇒ Do not mix Oxi-King™ chemicals with any other chemical or organic material.
- ⇒ NEVER use a fast-dissolving oxidizer in or near this product.
- ⇒ Be certain that water does not become contaminated with organics or by other chemicals from process leaks.
- ⇒ When handling the Brom Pac, avoid sparks, smoking or any open flame.

To obtain a replacement English manual or a Spanish manual, visit www.OxiKing.com or call 800-222-0169.

Versión en español disponible en www.OxiKing.com o llamando al 800-222-0169

Serial Number 1000

20-43-0069 553121543N